



# FIRST KLEAN™ 3900S™ SURFACE CLEANER



## GENERAL

### DESCRIPTION

A cleaner formulated to dry fast for initial surface preparation prior to sanding or bodywork. It is ideal for removing wax, grease, silicone, dirt, tar, insect remnants, road film and pinstripe adhesives.

**The products referenced herein may not be sold in your market. Please consult your distributor for product availability.**



## MIXING

### COMPONENTS

First Klean™ 3900S™ Surface Cleaner

### MIX RATIO

Ready to use



## APPLICATION

### SUBSTRATES

- Unsanded substrates
- OEM finishes
- Cured, repainted surfaces

**Do not use on unprimed plastic or fiberglass substrates due to possible static buildup, which may cause a flash fire.**

### SURFACE PREPARATION

Clean surface with mild detergent and water.

### APPLICATION

- Soak a clean cloth with First Klean™ 3900S™ Surface Cleaner.
- Wipe the surface to loosen and lift the contaminants; follow immediately by wiping thoroughly with a clean dry cloth.

**Local air districts may require the use of atomizing spray bottles for the application of cleaning solvent.**

### Tips for Success

- Do not allow First Klean™ 3900S™ Surface Cleaner to dry on the surface. If this does occur, simply re-wet and wipe dry.
- Use a clean cloth for applying and wiping First Klean™ 3900S™ Surface Cleaner.
- For hard to remove elements, reapply First Klean™ 3900S™ Surface Cleaner 3900S™ and allow it to sit on the surface for a few minutes without drying, and then wipe to loosen elements.
- For OEM or repainted surfaces that are known to be sensitive to repair, use 3949S™ Low VOC Cleaner.
- Close container after use. This prevents the cleaner from evaporating and losing strength.



## PHYSICAL PROPERTIES

All Values Ready To Spray

Max. VOC (LE):	778 g/L (6.5 lbs./gal)
Max. VOC (AP):	778 g/L (6.5 lbs./gal)
Avg. Gal. Wt.:	778 g/L (6.49 lbs./gal)
Avg. Wt.% Volatiles:	100.0%
Avg. Wt.% Exempt Solvent:	0.0%
Avg. Wt.% Water:	0.0%
Avg. Vol.% Exempt Solvent:	0.0%
Avg. Vol.% Water:	0.0%
Flash Point:	See MSDS / SDS

## VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

## SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and MSDS / SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: September 2014

In the United States:  
**1.855.6.AXALTA**  
**cromax.us**

In Canada:  
**1.800.668.6945**  
**cromax.ca**

