SYSTEM POSTER





S3110 / S3140 / S3170 SANDING SURFACER PLUS

STANDARD SANDING:

- High solids 2K surfacer developed to work with Syrox Basecoat
- Can be used independently or intermixed to give 5 surfacer shades ranging from white to black
- Easy sanding
- Excellent sag resistance





5:1 + 0-15% S6000 HS Activator Slow S6010 HS Activator Standard S6020 HS Activator Fast S6030 HS Activator Very Fast



ACCELERATED SANDING:

• Accelerated drying possible with S7300 Surfacer Additive Fast

NON-SANDING:

• Can be converted to non-sanding version through use of S3080 Non-Sanding Convertor





5:1 + 10-15% S6020 HS Activator Fast S6030 HS Activator Very Fast



3:1 + 45% S6000 HS Activator Slow S6010 HS Activator Standard S6020 HS Activator Fast

BASECOAT

- Accurate colour matching
- Simple mixing ratio



+20% S940 Basecoat Thinner For 3-Stage colours and interiors, activate basecoat with S6100

S5000 HS TOP CLEAR

- Flexible in application, can be applied in 1.5 coats continual process or 2 single coats with intermediate flash off
- Simple mixing ratio
- Delivers excellent appearance

S5100 HS AIR DRY CLEAR

• Ideal for spot, small and medium repairs up to 3 panels





2:1

S6030 HS Activator Very Fast S6020 HS Activator Fast S6010 HS Activator Standard S6000 Hs Activator Slow



2:1 S6010 HS Activator Standard

Efficient application process with no flash between coats
Fast air-drying capabilities, ready to polish in under 1 hour @ 20°C



SYROX



- Next generation high solids formulation but with lower RFU viscosity
- Easy application in 2 single coats with short intermediate flash off
- Fast drying, 15 20 minutes @ 60°C object temperature





2:1 +5% S6010 HS Activator

Standard

AXALTA COATING SYSTEMS AUSTRALA

D(+61) 02 8818 4300 info-anz@axalta.com



