

Corroless CCI 250

CORROSION INHIBITOR

Issue Date: June 2020
Code: LC00250
Page 1 of 2

Product Description	A concentrated, clear, water borne vapour phase corrosion inhibitor (VCI), developed as a hydro-test additive and for indoor use on steel			
Features & Use	<ul style="list-style-type: none"> Accepted onto the List of Approved Products suitable for use by the North Sea Oil and Gas industry, based on testing for its environmental impact. Subject to normal government restrictions, CCI 250 can be discharged into the marine environment Used extensively as a hydro-test additive Works by both vapour phase and contact inhibition and therefore protects above and below the water line. Active period up to 2 years depending on use. Can be applied to equipment in service, shutdown or preservation Applications include steel coils and stacks, steel components, pumps and valves internals, pipes, enclosed cooling water systems and radiators 			
Approvals/ Certification	<ul style="list-style-type: none"> OCNS Registration Number 1412 			
Finish	Soft oily translucent finish if allowed to dry out			
Volume Solids	30% ± 2%			
VOC Content	388 g/litre ± 20 g/litre			
Film Thickness Range And Coverage		Dry Film Thickness	Wet Film Thickness	Theoretical Coverage
	Nominal	20 µm	67 µm	15 m ² /litre
	Practical coverage depends on the application method, painting conditions and the shape and roughness of the surface to be coated			
Drying Times	Applied to 67 microns WFT	Dries to a soft oily film in 48 hours at 18°C		
Colours	Light amber liquid which dries to a translucent oily finish			
Mix Ratio	Single Pack: See application for further advice			
Pot Life	Not applicable			
SG	1.02 ± 2%			
Storage Conditions	Store in dry, cool conditions and protect from frost			
Shelf Life	Minimum 24 months if stored as above in unopened containers			
Flash Point	29°C			

Corroless CCI 250

Issue Date: June 2020
Page 2 of 2

Surface Preparation	For best results due to obvious dirt/grease contamination or suspected salt or chemical contamination, clean all surfaces with a water-soluble degreaser, wash down with clean fresh water and allow to dry before application
Mixing	Stir thoroughly before use.
Thinner / Cleaner	Use only fresh water.
Application Conditions	<ul style="list-style-type: none"> • Only apply in conditions of good ventilation which must be maintained during drying • Do not use below 2°C • Application Temperature Range 2°C-35°C
Application and Product Notes	<ul style="list-style-type: none"> • Apply by brushing, spraying, dipping, flooding or fogging • For hydrotest applications, CCI 250 should be added to water systems at a ratio of 2 to 10 parts CCI 250 to 100 parts of clean fresh water by volume depending on the quality of the water and protection requirements • Not recommended for use in sea water as protection is only minimal at best • CCI 250 may be introduced into a system by adding to the water • By spraying neat material directly onto components • By fogging neat material into void spaces (such as boilers) with compressed air or by any combination of the above. In order to extend the active period of the vapour phase protection, all normal vents, breather pipes and other openings should be sealed • In non-enclosed water systems, periodic recharging with CCI 250 is required to maintain a working concentration
Health & Safety	Containers are provided with safety labels which should be observed. Further information about hazardous influences and protection are detailed in individual Product Safety Data Sheets. A Safety Data Sheet for this product is available on request from Axalta Coating Systems.

AN AXALTA COATING SYSTEMS BRAND



The information provided herein corresponds to our knowledge on the subject at the date of its publication. This information may be subject to revision as new knowledge and experience becomes available. The data provided fall within the normal range of product properties and relate only to the specific material designated; these data may not be valid for such material used in combination with any other materials or additives or in any process, unless expressly indicated otherwise. The data provided should not be used to establish specification limits or used alone as the basis of design; they are not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of a specific material for your particular purposes. Since Axalta cannot anticipate all variations in actual end-use conditions Axalta makes no warranties and assumes no liability in connection with any of this information. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent rights. This product is for professional use only.