









# Axalta™ VS1000 Surface Cleaning Solvent

 <p>VS1000 Surface Cleaning Solvent</p> <p>COMPONENTS</p>	 <p>Hand wipe with saturated cloth</p> <p>APPLICATION</p>
 <p>Ready to Use</p> <p>MIX RATIO</p>	 <p>Wipe dry with clean cloth</p> <p>DRY TIME</p>
 <p>N/A</p> <p>VISCOSITY</p>	 <p>779 grams / liter 6.47 lbs / gallon</p> <p>VOC</p>



## GENERAL

### DESCRIPTION

VS1000 is a fast evaporating surface cleaner designed to safely and quickly removes oils, waxes, and silicones prior to applying topcoats. VS1000 is perfect for use around moldings and minor clean-up prior to priming or painting.

**The products referenced herein may not be sold in your market. Please consult your distributor for product availability.**



## APPLICATION

### APPLICATION

1. Saturate a clean, dry lint-free cloth with VS1000 and apply to small areas using a wiping motion.
2. Follow by wiping with a clean dry lint-free cloth.

VS1000 may also be used as a quick cleaner to remove fingerprints, smudge marks, and spot contaminants on small areas without the use of a second drying cloth.

## VOC REGULATED AREAS

VOC as Applied

779 grams/liter | 6.47 lbs/gallon

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.



---

## **SAFETY AND HANDLING**

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

**Revised: August 2020**

**In the United States and Canada:  
1.855.6.AXALTA  
Axalta.us**

