



# Axalta VS1100 Surface Cleaning Solvent

 VS1100 Surface Cleaning Solvent <b>COMPONENTS</b>	 Hand wipe with saturated cloth <b>APPLICATION</b>
 Ready to Use <b>MIX RATIO</b>	 Wipe dry with clean cloth <b>DRY TIME</b>
 N/A <b>VISCOSITY</b>	 0 grams / liter 0.00 lbs / gallon <b>VOC</b>



## GENERAL

### DESCRIPTION

VS1100 is a ready to use, 0.00 lbs/gal VOC waterborne surface cleaner designed specifically for areas with low VOC regulations. VS1100 is medium-drying and is designed to remove tar, wax, oil, grease, road grime, silicone, and surface contaminants prior to sanding or bodywork as well as pre-cleaning before applying topcoats. VS1100 may be used on bare metal without concern for immediate flash rusting and on plastic to minimize static build-up.

**The products referenced herein may not be sold in your market. Please consult your distributor for product availability.**



## APPLICATION

### APPLICATION

1. Saturate a clean, dry lint-free cloth with VS1100 Surface Cleaning Solvent and apply to one panel at a time or for large areas, apply to a 2' x 2' section to avoid premature drying.
2. Follow by wiping with a clean, lint-free cloth until dry. Be sure to wipe the surface completely clean and dry. If VS1100 is allowed to dry on the surface, re-apply and wipe until thoroughly dry.
3. In low temperature applications, be sure to dry the surface completely before applying primers or topcoats. Increasing room temperature or additional air movement may be used to speed up the solvent evaporation.

Note: Protect from freezing. Best used when temperatures are maintained at or above 70°F (21°C). Do not use on solvent sensitive substrates.



---

## VOC REGULATED AREAS

VOC as Applied

0 grams/liter | 0.00 lbs/gallon

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

---

## SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and SDS precautions. If mixed with other components, mixture will have hazards of all components. Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

**Revised: November 2020**

In the United States and Canada:

**1.855.6.AXALTA**

**Axalta.us**

