









Axalta™ VS1200 Anti-Static Degreaser

 <p>COMPONENTS</p> <p>VS1200 Anti-Static Degreaser</p>	 <p>APPLICATION</p> <p>Hand wipe with saturated cloth</p>
 <p>MIX RATIO</p> <p>Ready to Use</p>	 <p>DRY TIME</p> <p>Flash until dry</p>
 <p>VISCOSITY</p> <p>N/A</p>	 <p>VOC</p> <p>443 grams / liter 3.7 lbs / gallon</p>



GENERAL

DESCRIPTION

Axalta VS1200 Anti-Static Degreaser is a specifically formulated solvent blend that has been designed to prevent the build-up of static. Recommended for use on substrates prone to static build-up such as plastic bumper covers (polypropylene).

Package Sizes

- 1 quart (0.94 liters)



APPLICATION

APPLICATION

Wipe VS1200 using a saturated wipe followed by a clean lint free cloth. Wipe in one direction only. Wiping in a back & forth motion may cause additional static.

VS1200 may be applied with a spray gun, allow to flash off, to help eliminate static.

VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and SDS precautions. If mixed with other components, mixture will have hazards of all components.



Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: November 2020

**In the United States and Canada:
1.855.6.AXALTA
Axalta.us**

