



FINAL KLEAN™ 3901S™ SURFACE CLEANER



GENERAL

DESCRIPTION

A cleaner formulated to dry fast for final surface preparation prior to painting. It ideal for removing sanding sludge, dust, fingerprints, and small amounts of grease and oil.

The products referenced herein may not be sold in your market. Please consult your distributor for product availability.



MIXING

COMPONENTS

Final Klean™ 3901S™ Surface Cleaner

MIX RATIO

Ready to use



APPLICATION

SUBSTRATES

- Sanded substrates
- OEM finishes
- Cured, repainted surfaces
- Sanded primers
- Cured sealers

Do not use on unprimed plastic or fiberglass substrates due to possible static buildup, which may cause a flash fire.

SURFACE PREPARATION

Use First Klean™ 3900S™ Surface Cleaner, Prep-Sol® 3919S™ Cleaning Solvent, or 3949S™ Low VOC Cleaner to remove wax and grease prior to sanding.

Local air districts may require the use of atomizing spray bottles for the application of cleaning solvent.

APPLICATION

- Soak a clean cloth with Final Klean™ 3901S™ Surface Cleaner.
- Wipe the surface to loosen and lift the contaminants; follow immediately by wiping thoroughly with a clean dry cloth.

Tips for Success

- Do not allow Final Klean™ 3901S™ Surface Cleaner to dry on the surface. If this does occur, simply re-wet and wipe dry.
- Use a clean cloth for applying and wiping Final Klean™ 3901S™ Surface Cleaner.
- Close container after use. This prevents the cleaner from evaporating and losing strength.



PHYSICAL PROPERTIES

All Values Ready To Spray

Max. VOC (LE):	727 g/L (6.1 lbs./gal)
Max. VOC (AP):	727 g/L (6.1 lbs./gal)
Avg. Gal. Wt.:	727 g/L (6.07 lbs./gal)
Avg. Wt.% Volatiles:	100.0%
Avg. Wt.% Exempt Solvent:	0.0%
Avg. Wt.% Water:	0.0%
Avg. Vol.% Exempt Solvent:	0.0%
Avg. Vol.% Water:	0.0%
Flash Point:	See MSDS/SDS

VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and MSDS/SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: September 2014

In the United States:
1.855.6.AXALTA
cromax.us

In Canada:
1.800.668.6945
cromax.ca

