

Low VOC Chart



For the Bay Area AQMD - Regulation 8 Rule 45
 Motor Vehicle and Mobile Equipment Coating Operations

Revised: May 2021

Effective: October 1, 2009

Surface Preparation - VOC Limit: 25 g/L (0.21 lbs./gal.)						
CODE	DESCRIPTION	REMARKS	MIX RATIO			APPLIED VOC
1760	Cleaner		Ready To Use			24 g/L
2010	Cleaner		Ready To Use			0 g/L
2040	Cleaner		Ready To Use			0 g/L
2571	Cleaner		Ready To Use			24 g/L
4040	Cleaner		Ready To Use			0 g/L
8007	Cleaner		Ready To Use			0 g/L
2050	Cleaner	*Note in Footer	Ready To Use			947 g/L
Primer - VOC Limit: 250 g/L (2.1 lbs./gal.)						
CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
6811	Gray Primer		4:1	6896	-	250 g/L
901	Gray Polyester Primer		1:2.5 oz.	998	-	250 g/L
903	Black Polyester Primer		1:2.5 oz.	998	-	250 g/L
905	Buff Polyester Primer		1:2.5 oz.	998	-	250 g/L
907	White Polyester Primer		1:2.5 oz.	998	-	250 g/L
922	Gray Primer		1:1	2010	-	250 g/L
941	Polyester Primer		4:1	9498	-	250 g/L
Primer Sealer - VOC Limit: 250 g/L (2.1 lbs./gal.)						
CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
6711	Gray Epoxy Primer Sealer		2:1	6796	-	250 g/L
6713	Charcoat Epoxy Primer Sealer		2:1	6796	-	250 g/L
Single Stage Topcoats - VOC Limit: 340 g/L (2.8 lbs./gal.)						
CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
2513	Satin Black		4:1	2696	-	340 g/L
2713	Flat Black		4:1	2696	-	340 g/L
2813	Eurocoat Black		4:1:2	2896	8025/8050/8075/8100	340 g/L
2817	Eurocoat White		4:1:2	2896	8025/8050/8075/8100	340 g/L
Clearcoat - VOC Limit: 250 g/L (2.1 lbs./gal.)						
CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
2210	Ultra Auto Clearcoat		4:1	2294	-	250 g/L
2594	Satin Urethane Clearcoat		4:1	2696	-	250 g/L
2610	Super Pro Clearcoat		4:1	2696	-	250 g/L
2623	Flat Clearcoat		4:1	2696	-	250 g/L

*Gun & equipment cleaner only, specific equipment for collecting and minimizing evaporation must be used.

Additional additives/components may be used, please consult TDS for usage and recommendations.

All VOC (LE) values listed are maximum Ready-to-Spray in pounds per gallon.