



Permahyd® Sanding Paste 1120



GENERAL

DESCRIPTION

A water-thinnable, sanding paste, suitable for the perfect preparation of blending areas.

Permahyd® Sanding Paste 1120's unique micro crystals create a homogeneous, flat surface.

The products referenced herein may not be available for sale in your market. Please consult your distributor for product availability.



MIXING

COMPONENTS

Permahyd® Sanding Paste 1120

MIX RATIO

Ready-to-use

SPECIAL TIPS

1. Do not allow Permahyd® Sanding Paste 1120 to dry on the surface.
2. Thoroughly clean and scuff the entire blend area.
3. Do not use this product on a buffing wheel.
4. Always use a clean scuff pad.
5. Permahyd® Sanding Paste 1120 is not suitable for TPA.
6. Permahyd® Sanding Paste 1120 is not to be used for cleaning raw plastic.



APPLICATION

SUBSTRATES

Through-hardened 2K Finish for blending

APPLICATION

- Before further treatment, clean with Permaloid® Silicone Removers 7087 or 7010 Slow, or Permahyd® Silicone Remover 7085, or Permahyd® Silicone Remover 7096.
- Use the sanding paste in conjunction with warm water and a gold or gray scuff pad.
- Clean and sand the entire blend area with paste and scuff pad.
- Rinse thoroughly with water and then dry.
- Clean again with Permaloid® Silicone Removers 7087 or 7010 Slow, or Permahyd® Silicone Remover 7085, or Permahyd® Silicone Remover 7096.
- Apply complaint Spies Hecker Topcoat.



PHYSICAL PROPERTIES

Coating Category: Surface Preparation
 Max. VOC (AP): 60 g/l; 0.5 lbs/gal
 Max. VOC (LE): 168 g/l; 1.4 lbs/gal
 Avg. Gallon Weight: 1384.9 g/l; 11.56 lbs/gal
 Avg. Weight % Volatiles: 51.9 %
 Avg. Weight % Water: 47.7%
 Avg. Weight % Exempt Solvent: 0.0%
 Avg. Volume % Water: 66.2%
 Avg. Volume % Exempt Solvent: 0.0%

Theoretical Coverage: 440.6 sq. ft. @ 1 mil

VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and MSDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Any analytical results set forth herein do not constitute a warranty of specific product features or of the product's suitability for a specific purpose. All products are sold pursuant to our general conditions of sale. We hereby disclaim all warranties and representations, express or implied, with respect to this product, including any warranty of merchantability or fitness for a particular purpose. This product is protected by patent law, trademark law, copyright law, international treaties and/or other applicable law. All rights reserved. Unauthorized sale, manufacturing or use may result in civil and criminal penalties.

Revised: June 2016

