



Permaloid® Silicone Remover 7087 (Spray Can)



GENERAL

DESCRIPTION

An excellent, residue-free solvent cleaner for the removal of silicone, bugs, tar, grease, and wax from sanded, old or original finishes, and surfaces coated with primer or surfacer that have been sanded.

Permaloid® Silicone Remover 7087 is available as an aerosol only.

The products referenced herein may not be available for sale in your market. Please consult your distributor for product availability.



MIXING

COMPONENTS

Permaloid® Silicone Remover 7087

MIX RATIO

Ready-to-spray

SPECIAL TIPS

1. Shake well before using.
2. Always use a clean cloth when wiping away Permaloid® Silicone Remover 7087.
3. Do not allow Permaloid® Silicone Remover 7087 to dry on the surface.
4. Allow cleaned surfaces to dry completely before recoating.
5. Heavily soiled areas need to be cleaned more than once.
6. Permaloid® Silicone Remover 7087 should not be used to clean plastics or fiberglass due to possible static buildup.
7. This product is not suitable for cleaning spray guns or tools or for removing release agents from plastic parts.



APPLICATION

FIELD OF APPLICATION

For cleaning surfaces prior to applying primers, surfacers, or top coats.

PROCEDURE

- Apply Permaloid® Silicone Remover 7087.
- Wipe dry with a clean cloth before Permaloid® Silicone Remover 7087 evaporates.



DRY TIMES

AIR DRYING

Slow evaporating.



PHYSICAL PROPERTIES

Coating Category: Surface Preparation
 Max. VOC (AP/LE): 903 g/l; 7.5 lbs/gal
 Avg. Gallon Weight: 902.8 g/l; 7.53 lbs/gal
 Avg. Weight % Volatiles: 100 %
 Avg. Weight % Water: 0.0%
 Avg. Weight % Exempt Solvent: 0.0 %
 Avg. Volume % Water: 0.0%
 Avg. Volume % Exempt Solvent: 0.0

VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and MSDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Any analytical results set forth herein do not constitute a warranty of specific product features or of the product's suitability for a specific purpose. All products are sold pursuant to our general conditions of sale. We hereby disclaim all warranties and representations, express or implied, with respect to this product, including any warranty of merchantability or fitness for a particular purpose. This product is protected by patent law, trademark law, copyright law, international treaties and/or other applicable law. All rights reserved. Unauthorized sale, manufacturing or use may result in civil and criminal penalties.

Revised: December 2015

