



Priomat® Plastic Cleaner 8581



GENERAL

DESCRIPTION

A slow evaporating organic solvent mixture used primarily to remove oil and grease residues from plastic surfaces prior to applying primers, surfacers, or top coats.

The products referenced herein may not be sold in your market. Please consult your distributor for product availability.



MIXING

COMPONENTS

Priomat® Plastic Cleaner 8581

MIX RATIO

Ready-to-use

SPECIAL TIPS

1. Do not allow Priomat Plastic Cleaner 8581 to dry on the surface.
2. This product is not suitable for cleaning spray guns or tools.
3. Always use a clean cloth to wipe away Priomat Plastic Cleaner 8581.
4. Heavily soiled areas must be cleaned twice.
5. Final clean prior to use of any Permahyd product with:
 - a. Permaloid® Silicone Removers 7087 or 7010 Slow, or Permahyd Silicone Remover 7085, 7086 or 7096.
 - b. Axalta™ Silicone Remover 200 Slow, Axalta Silicone Remover 205A Spray, Axalta Silicone Remover 210 Water or Axalta Silicone Remover 220 Low VOC.
6. Allow cleaned surfaces to dry completely before recoating.



APPLICATION

- Apply Priomat Plastic Cleaner 8581 with a spray bottle and wipe with clean cloth.
- Wipe dry with a clean cloth before Priomat Plastic Cleaner 8581 evaporates.



PHYSICAL PROPERTIES

Coating Category: Surface Preparation
 Max. VOC (AP): 858 g/l; 7.1 lbs/gal
 Max. VOC (LE): 858 g/l; 7.1 lbs/gal
 Avg. Gallon Weight: 859.1 g/l; 7.17 lbs/gal
 Avg. Weight % Volatiles: 100%
 Avg. Weight % Water: 0.1%
 Avg. Weight % Exempt Solvent: 0.0%
 Avg. Volume % Water: 0%
 Avg. Volume % Exempt Solvent: 0.0%

VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.



SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Any analytical results set forth herein do not constitute a warranty of specific product features or of the product's suitability for a specific purpose. All products are sold pursuant to our general conditions of sale. We hereby disclaim all warranties and representations, express or implied, with respect to this product, including any warranty of merchantability or fitness for a particular purpose. This product is protected by patent law, trademark law, copyright law, international treaties and/or other applicable law. All rights reserved. Unauthorized sale, manufacturing or use may result in civil and criminal penalties.

Revised: September 2019

In the United States: In Canada:
1.855.6.AXALTA | 1.800.668.6945
spieshecker.us | spieshecker.ca

