


Standex[®] 2K Plasticiser



Ordering Information:

1 Liter	2K Plasticiser	020 15260
---------	----------------	-----------

Features:

- ✧ Universal plasticiser for all Topcoat systems
- ✧ Also suitable for Standox 2K Fillers
- ✧ High, long term elasticity


Working Process: Elastic Additive

Substrates:

- ✓ Standox Basecoats
- ✓ Standoblue[®] Basecoats



For substrate preparation information see **Standex** Painting System S1!



Mix **Standex** 2K Clearcoat, **Standex** 2K Filler or **Standex** 2K Sealer with **Standex** 2K Plasticiser according to the appropriate TDS.

Important Technical Remarks:

- Do not store 2K Fillers which are plasticised. Only mix prior to use.
- To optimize the sanding properties the **Standex** 2K Fillers should be dried 45 min/ 140°F (60°C) panel temperature.
- Do not use **Standex** 2K Plasticiser in Basecoat. If additional flex is needed, add 15% Hardener.
- Pay close attention to proper flash off times before baking to avoid solvent popping.
- Always add plasticiser before the addition of hardener.

Important Legislative Remarks:

- Please see the appropriate VOC Wallchart for compliance for your area.
- **For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and MSDS precautions. If mixed with other components, mixture will have hazards of all components. Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates. Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.**
- Any analytical results set forth herein do not constitute a warranty of specific product features or of the product's suitability for a specific purpose. All products are sold pursuant to our general conditions of sale. We hereby disclaim all warranties and representations, express or implied, with respect to this product, including any warranty of merchantability or fitness for a particular purpose. This product is protected by patent law, trademark law, copyright law, international treaties and/or other applicable law. All rights reserved. Unauthorized sale, manufacturing or use may result in civil and criminal penalties.