



3800S™ Surface Cleaner



GENERAL

DESCRIPTION

A cleaning solvent specifically designed to remove wax, grease, silicone, dirt, tar, insect remnants, road film and pinstripe adhesives from the surface.

The products referenced herein may not be sold in your market. Please consult your distributor for product availability.



MIXING

COMPONENTS

3800S Surface Cleaner

MIX RATIO

Ready-to-use



APPLICATION

SUGGESTED USES

- All Commercial Transportation topcoats
- Sanded substrates
- OEM finishes
- Cured, repainted surfaces
- Sanded primers

NOT RECOMMENDED FOR

Do not use on unprimed plastic or fiberglass substrates due to possible static buildup, which may cause a flash fire.

SURFACE PREPARATION

Clean surface with mild detergent and water.

APPLICATION

- Soak a clean cloth with 3800S Surface Cleaner.
- Wipe the surface while it is still wet to loosen and lift the contaminants. Follow immediately by wiping thoroughly with a clean, dry cloth.

Local air districts may require the use of atomizing spray bottles for the application of cleaning solvent.

Tips for Success

- Do not allow 3800S Surface Cleaner to dry before removing from the surface. For hard to remove contaminants, re-apply and allow 3800S to rest on the surface for a few minutes without drying, and then wipe to loosen contaminants.
- Clean hard to remove tar and grime with a mild detergent prior to using 3800S Surface Cleaner.
- Use a clean cloth for applying and wiping 3800S Surface Cleaner.
- For OEM or repainted surfaces that are known to be sensitive to repair, use 3821S™ Low VOC Cleaner



PHYSICAL PROPERTIES

Weight Per Gallon (component only)	6.51 lbs.
Weight Per Liter (component only)	780 grams
Flash Point (Closed Cup)	See MSDS/SDS
Shelf Life	12 months minimum

Ready to Use:

Gallon Weight pounds per gallon	6.51
Gallon Weight grams per liter	780
VOC AP pounds per gallon - Maximum	6.5
VOC AP grams per liter - Maximum	780
Weight Solids	0.0%
Volume Solids	0.0%
Weight Water	0.0%
Volume Water	0.0%
Weight Exempt Solvents	0.0%
Volume Exempt Solvents	0.0%
Theoretical Coverage per RTS Gallon at 1 mil DFT	Not Applicable

VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and MSDS/SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: June 2015

In the United States:
1.855.6.AXALTA
axalta.us

In Canada:
1.800.668.6945
axalta.ca

