



3821S™ Low VOC Cleaner



GENERAL

DESCRIPTION

A 0.21 lb. /gal (25 g/l) category compliant, multi-purpose surface cleaner designed to leave no surface residue. Its unique formulation makes it excellent for dissolving water-soluble and light surface contamination. It is intended to dry quickly and not affect tape or paint adhesion.

PRODUCT ADVANTAGES

- Low VOC composition
- Works well on dirt, insect remnants, bird droppings, tree sap, salt/road film, tape adhesives, finger prints and compound sludge

The products referenced herein may not be sold in your market. Please consult your distributor for product availability.



MIXING

COMPONENTS

3821S Low VOC Cleaner

MIX RATIO

Ready-to-use. Shake well before using.



APPLICATION

SUGGESTED USES

- All Commercial Transportation topcoats
- Sanded substrates
- OEM finishes
- Cured, repainted surfaces
- Sanded primers

NOT RECOMMENDED FOR

Substrates that have not been thoroughly cleaned of heavy contamination (grease, wax, oil, etc.)

APPLICATION

- Soak a clean cloth with 3821S Surface Cleaner or spray 3821S Surface Cleaner on the surface thoroughly with a spray bottle.
- Wipe the surface while it is still wet to loosen and lift the contaminants. Follow immediately by wiping thoroughly with a clean, dry cloth.
- For hard to remove surface contamination, reapply 3821S Surface Cleaner and wipe off with a clean, dry cloth.

STORAGE

Store 3821S Surface Cleaner at room temperature. Do not store in areas subject to freezing temperatures.



PHYSICAL PROPERTIES

Weight Per Gallon (component only)	8.01 lbs.
Weight Per Liter (component only)	960 grams
Flash Point (Closed Cup)	See MSDS/SDS
Shelf Life	12 months minimum

Ready to Use:

Gallon Weight pounds per gallon	8.01
Gallon Weight grams per liter	960
VOC AP pounds per gallon - Maximum	0.2
VOC AP grams per liter - Maximum	25
Weight Solids	0.0%
Volume Solids	0.0%
Weight Water	83.0%
Volume Water	80.0%
Weight Exempt Solvents	15.0%
Volume Exempt Solvents	18.0%
Theoretical Coverage per RTS Gallon at 1 mil DFT	Not Applicable

VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and MSDS/SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: June 2015

In the United States:
1.855.6.AXALTA
axalta.us

In Canada:
1.800.668.6945
axalta.ca

