



EPA Rule Test Answer Key

EPA RULE 40 CFR PART 63 SUBPART HHHHHH TRAINING REVIEW

ANSWER KEY

1. A technician paints cars and light trucks at a local collision center. Is this technician required to have documented training under EPA Rule 40 CFR Part 63?
 - Yes
 - No

2. Which of the following help improve transfer efficiency?
 - Spray gun set-up
 - Gun distance
 - Spray overlap
 - All these

3. Where can coatings be sprayed under EPA Rule 40 CFR Part 63?
 - Open shop floor
 - Enclosed prep stations
 - Enclosed booths
 - Outdoors

4. How may spray guns be cleaned under this EPA Rule?
 - Spraying solvent into booth filter
 - Enclosed gun cleaner or by hand

5. Does my shop have to notify the EPA that we are compliant to EPA Rule 40 CFR Part 63?
 - Yes
 - No

6. How often is painter recertification required?
 - Every 2 years
 - Every 3 years
 - Every 4 years
 - Every 5 years

7. Is a facility that does not apply products containing target HAPs automatically exempt from this rule?
 - Yes
 - No

8. Are non-refillable aerosols exempt from this rule?

Yes

No

9. This rule requires my shop to document that the spray booth filters have 98% or greater efficiency

Yes

No

10. Proper overlap for spray coatings is

45% - 55%

55% - 65%

65% - 75%

75% - 85%

In the United States:
1.855.6.AXALTA
axalta.us

In Canada:
1.800.668.6945
axalta.ca

