

Low VOC Chart

For Canadian National Rule
Canada Gazette Part II, Volume 143, No 14
Effective: June 18, 2010



Revised: March 18, 2020

Cleaner VOC Limit 50 g/L (.42 lb/gal)						
CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	APPLIED VOC
105™	Cleaner	Equipment Cleaner	Ready to Use	-	-	650 g/L **
130™	Cleaner		Ready to Use	-	-	0 g/L
200™	Silicone Remover Slow	Used as a spot cleaner only in a hand-held spray bottle prior to sanding	Ready to Use	-	-	779 g/L **
205A™	Silicone Remover Spray	Aerosol cleaners (non-refillable) †	Ready to Use	-	-	759 g/L **
220™	Silicone Remover Low VOC		Ready to Use	-	-	20 g/L
225™	Bug & Tar Remover	Used as a spot cleaner only in a hand-held spray bottle prior to sanding	Ready to Use	-	-	347 g/L **
265™	Plastic Cleaning Paste	Plastic Surface Cleaner	Ready to Use	-	-	24 g/L
275™	Plastic Cleaning Solvent	Used as a spot cleaner only in a hand-held spray bottle prior to sanding	Ready to Use	-	-	863 g/L **
2310S™	Plastic Cleaning Paste	Plastic Surface Cleaner	Ready to Use	-	-	13 g/L
3642SC™	Cleaner	Equipment Cleaner	Ready to Use	-	-	764 g/L **
3900S™	Cleaner	Used as a spot cleaner only in a hand-held spray bottle prior to sanding	Ready to Use	-	-	780 g/L **
3919SC™	Cleaner	Used as a spot cleaner only in a hand-held spray bottle prior to sanding	Ready to Use	-	-	783 g/L **
4105S™	Cleaner	Used as a spot cleaner only in a hand-held spray bottle prior to sanding	Ready to Use	-	-	738 g/L **
A-2320S™	Cleaner	Aerosol cleaners (non-refillable) †	Ready to Use	-	-	695 g/L **
A-39X0S	Cleaner	Aerosol cleaners (non-refillable) †	Ready to Use	-	-	790 g/L **
V-3921S™	Cleaner		Ready to Use	-	-	25 g/L
Adhesion Promoter VOC Limit 840 g/L (7.0 lb/gal)						
CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
A-2330S™	Adhesion Promoter	Non-refillable aerosol †	Ready to Use	-	-	See remarks
2322S™	Adhesion Promoter		-	-	-	791 g/L
2330S™	Adhesion Promoter		-	-	-	791 g/L
Pretreatment VOC Limit 660 g/L (5.5 lb/gal)						
CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
22880S™	Etch Primer		2:1	2280XS	-	660 g/L
A-411XS	Self-Etching Primer	Non-refillable aerosol †	Ready to Use	-	-	See remarks
CF-5717S™	Metal Conditioner		1:2	-	Water	660 g/L
PS4000™	Pretreatment Wipes		Ready to Use	-	-	660 g/L
Primer Surfacer VOC Limit 250 g/L (2.1 lb/gal)						
Additional additives may be used. Consult technical data sheet for usage and compliance.						
CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
LE3004S™	Primer Surfacer		4:1	LE30X5S	-	250 g/L
LE3130S™	UVA Primer Surfacer		Ready to Use	-	-	250 g/L
LE350XS	Primer Filler		5:1:1	LE100XS	LE10X5S	250 g/L
A-3130S™	UVA Primer Surfacer (Aerosol)	Non-refillable aerosol †	Ready to Use	-	-	See remarks
A-42X0S	Primer (Aerosol)	Non-refillable aerosol †	Ready to Use	-	-	See remarks
Primer Sealer VOC Limit 340 g/L (2.8 lb/gal)						
Additional additives may be used. Consult technical data sheet for usage and compliance.						
CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
LE27X0S	Primer Sealer		2:1:0-10%	LE2705S™	LE1075S™	340 g/L
LE30X0S	Primer Sealer		3:1	LE30X5S	-	340 g/L
LE35X0S	Sealer		5:1:1	LE100XS	LE12X5S	340 g/L
V-29X0S	Primer		2:1	V-290XS	-	340 g/L
Single Stage Coating VOC Limit 420 g/L (3.5 lb/gal)						
CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
A-5099S™	1K Bumper & Trim	Non-refillable aerosol †	Ready to Use	-	-	See remarks
Colour Coating VOC Limit 420 g/L (3.5 lb/gal)						
Additional additives may be used. Consult technical data sheet for usage and compliance.						
QUALITY	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
B Quality	Cromax® Mosaic™ Basecoat		1:2	-	SBL66XXS	420 g/L
CP Quality	Cromax® Pro Basecoat	† Mix ratio note in footer	†	-	WB204X	420 g/L
EZ Quality	Cromax® EZ Basecoat		1:20%	-	EZ240™	420 g/L
A-SBL6627S™	Mosaic™ Fill In Can (Aerosol)	Non-refillable aerosol †	†	-	-	See remarks
1000XS	Cromax® Midcoat		2:1	LE11X5S	-	420 g/L
Clearcoat VOC Limit 250 g/L (2.1 lb/gal)						
Additional additives may be used. Consult technical data sheet for usage and compliance.						
CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
LE5100S™	Clearcoat		2:1	LE11X5S	-	250 g/L
LE5400S™	Clearcoat		4:1	LE11X0S	-	250 g/L
LE5600S™	Clearcoat		4:1:1	LE5605S™	LE56X5S	250 g/L
LE8300S™	Clearcoat		3:1:1	LE100XS	LE10X5S	250 g/L
LE8700S™	Clearcoat		3:1	LE100XS	-	250 g/L
A-7480S™	Trim & Jamb Clearcoat (Aerosol)	Non-refillable aerosol †	Ready to Use	-	-	See remarks
Uniform Finish Coating or Blender VOC Limit 540 g/L (4.5 lb/gal)						
CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
WB209XS	Basecoat Blender	¥ Mix ratio note in footer	¥	-	-	540 g/L
SBL877S™	Basecoat Blender	§ Mix ratio note in footer	1:2:6	-	SBL66XXS	540 g/L
19301S™	Clearcoat Blender	Add up to 50% 19301S™ to 2.1 VOC clearcoat	-	-	-	540 g/L
790™	Clearcoat Blender	Non-refillable aerosol †	Ready to Use	-	-	See remarks
Other components that may be used (list is not all-inclusive). Consult technical data sheet for usage and compliance.						
CODE	DESCRIPTION	CODE	DESCRIPTION			
V-2350S™	Flex Additive					
389S™	Accelerator	19379S™	Application Enhancer			
V-389S™	Accelerator					
V-459S™	Anti-Cratering Additive	8989S™	Accelerator			
Non-coatings not impacted by Rule 307-354						
CODE	DESCRIPTION	CODE	DESCRIPTION			
2311S™	Sanding Paste	-	-			

† Please see Technical Data Sheet for usage and mixing recommendation; non-refillable aerosol products are excluded.

¥ Options: 1) Ready to spray; 2) +10% WB2040™ / WB2045™; 3) As above with up to 5% WB2095™

† Add 10-20% WB2040™ / WB2045™ for solid colors. Add 20-30% for effect and metallic colors.

*Less Water, Less Exempt. All VOC (LE) values listed are Maximum Ready-to-Spray in grams per liter.

** Excluded Product from the Automotive Refinishing VOC Regulations

X = 1, 2, 3, 4, 5, 6, 7, 8, 9

§ Add 200% SBL877S™ Blender to ready to spray Mosaic™ Basecoat.