

# VOC CHART

For the State of Rhode Island | Reg.30 - Automobile Refinishing Operations  
Group 2 Vehicles : See footer



Effective date: March 31, 1994

Revised: Dec 2020

## Surface Preparation: VOC Limit = 1.4 lbs./gal. (168 g/L)

CODE	DESCRIPTION	MIX RATIO	APPLIED VOC	CODE	DESCRIPTION	MIX RATIO	APPLIED VOC
107™	Low VOC Cleaner	RFU	0.2	3909S™	Cleaner	RFU	0.5
130™	Cleaner	RFU	0.0	3949S™	Cleaner	RFU	0.4
V-3921S™	Cleaner	RFU	0.2	210™	Axalta Silicone Remover Water	RFU	1.4
265™	Axalta Plastic Cleaning Paste	RFU	0.2	220™	Axalta Silicone Remover Low VOC	RFU	0.2

## Plastic Surface Preparation: VOC Limit = 6.5 lbs./gal. (780 g/L) - Plastic surfaces only!

CODE	DESCRIPTION	MIX RATIO	APPLIED VOC	CODE	DESCRIPTION	MIX RATIO	APPLIED VOC
A-3970S™	Aerosol Cleaner	RFU	6.4	2320S™	Plastic Cleaner	RFU	6.5
3901S™	Final Klean	RFU	6.1	3919S™	Cleaner	RFU	6.5
3900S™	Cleaner	RFU	6.5	106™	Cleaner	RFU	4.4
105™	Thinner	RFU	5.4	108™	Low Hap Cleaner	RFU	3.9
2319S™	Plastic Preparation	RFU	5.5	231XS	Plastic Paste	RFU	0.5
A-2320S™	Plastic Cleaner (Aerosol)	RFU	5.8	139™	Bug & Tar Remover	RFU	2.9
A-3990S™	Surface Cleaner High Temperature (aerc	RFU	6.4	200™	Axalta Silicone Remover Slow	RFU	6.5
				205A™	Axalta Silicone Remover Spray	RFU	6.2

## Specialty Coatings: VOC Limit = 7.0 lbs./gal. (840 g/L) - Consult Technical Data Sheet for usage.

CODE	DESCRIPTION	MAX APPLIED VOC (LE)	CODE	DESCRIPTION	MAX APPLIED VOC (LE)
19301S™	Clearcoat Blender	7.0	236XS	Matting Agent	7.0
A-300S™	Vinyl Fill In Can (Aerosol)	n/a	2370S™	Matted Clearcoat	7.0
222S™	Mid-Coat Adhesion Promoter	7.0	4531S™	Flattener	7.0
7601S™	Uniform Finish	7.0	69301S™	Basecoat Blender	7.0
2322S™	Plastics Adhesion Promoter	7.0	790™	Axalta Blender (Aerosol)	n/a
2330S™	Plastics Adhesion Promoter	7.0	A-2330S™	Polyolefin Adhesion Promoter (Aerosol)	n/a
234XS	Flexible Adhesion Sealer	7.0	JV Color	Vinyl Color System (JV Quality)	7.0
WB209X	Basecoat Blender	7.0	SBL877S™	Basecoat Blender	7.0
A-5099S™	1K Bumper & Trim (Aerosol)	n/a	305™	Axalta Plastic Polyolefin Adhesion Promoter Low VOC	7.0
715™	Axalta Sanding Paste	7.0	310A™	Axalta Plastic Polyolefin Adhesion Promoter	n/a
705™	Axalta 1K Fine Putty	7.0	320™	Axalta Plastic Primer Surfacer Black	7.0
766A™	Axalta 1K Trim Black Satin (Aerosol)	n/a	330™	Axalta Plastic Primer Surfacer Gray	7.0

## Pretreatments: VOC limit = 6.5 lbs./gal. (780 g/L)

CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
400A™	Axalta 1K Primer Surfacer Dark Gray (Aerosol)		RTS	-	-	n/a
410A™	Axalta 1K Primer Surfacer Light Gray (Aerosol)		RTS	-	-	n/a
420™	Axalta Etch Primer		1:1	421	-	6.5
495™	Axalta Metal Pretreatment Wipes		RTU	-	-	6.5
225S™	Aluminum Metal Cleaner - Step A		1:2	-	water	6.5
226S™	Aluminum Conversion Coating - Step B		RTS	-	-	0.0
22880S™	Low VOC Etch Primer		2:1	2280XS	-	6.5
244S™	Pretreatment		RTS	-	-	6.5
5717S™	Metal Conditioner		1:2	-	water	6.5
5718S™	Conversion Coating		RTS	-	-	0.0
615S™	Self-Etching Primer		1:1	-	61XS / 620S™	6.5
A-411XS	Etch Primer (Aerosol)		RTS	-	-	n/a
CF-5717S™	Metal Conditioner		1:2	-	water	6.5
PS4000™	Pretreatment Wipes		RTU	-	-	6.5

## Primer / Primer-Surfacers: VOC Limit = 2.8 lbs./gal. (340 g/L)

Other additives may be used. Consult technical data sheet for usage requirements.

CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
460A™	Axalta Epoxy 2K		RTS	-	-	n/a
A-3130S™	UVA Primer-Surfacer (Aerosol)		RTS	-	-	n/a
A-42X0S	Primer (Aerosol)		RTS	-	-	n/a
LE3004S™	Primer Surfacer		4:1	LE30X5S	-	2.8
LE3130S™	UV Primer Surfacer		RTS	-	-	2.8
LE340XS	Primer Filler		4:1	LE11X5S	-	2.8
LE350XS	Primer Filler		5:1:1	LE100XS	LE10X5S	2.8

## Primer-Sealer VOC Limit = 3.5 lbs./gal. (420 g/L)

Other additives may be used. Consult technical data sheet for usage requirements.

CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
LE27X0S	Primer Sealer		2:1:0-10%	LE2705S™	LE1075S™	3.5
LE30X0S	Primer Sealer		3:1	LE30X5S	-	3.5
LE32X0S	Waterborne 2K Sealer		1:5%	WB2075™	-	3.5
LE35X0S	Primer Sealer		5:1:1	LE100XS	LE10X5S	3.5
V-29X0S	Primer Sealer		2:1	V-290XS	-	3.5
V-4940S™	Primer Sealer		3:1	V-49X5S	-	3.5

## Multi-Stage Topcoats: VOC Limit = 3.5 lbs./gal. (420 g/L)

Please consult Technical Data Sheet for compliant clearcoat recommendation along with any additional additives that may be used.

CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
CP Quality	Cromax® Pro Basecoat		1:10%-30%	-	WB2040™ / WB2045™	3.5
B Quality	Cromax® Mosaic™ Basecoat		1:2	-	SBL66XXS	3.5
K Quality	ChromaBase® Basecoat		1:1:6.25%	71X5S	1430XS / 77X5S	3.5
F Quality	ChromaPremier® Basecoat		1:1:6.25%	71X5S	1430XS / 77X5S	3.5
FX Quality	ChromaLusion® Basecoat		1:1:6.25%	71X5S	12305S™	3.5
A-7160S™	SprayBase™ Fill In Can (Aerosol)	⚠ - See footer	-	-	-	See Remarks
A-SBL6627S™	Mosaic™ Fill In Can (Aerosol)	⚠ - See footer	-	-	-	See Remarks
EZ Quality	Cromax® EZ Basecoat		1:20%	-	EZ240™	3.5

## Multi-Stage Topcoats: VOC Limit = 3.5 lbs./gal. (420 g/L)

Please consult Technical Data Sheet for compliant basecoat recommendation along with any additional additives that may be used.

CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
A-7480S™	Clearcoat (Aerosol)	Exempt: Non-refillable aerosol products	RTS	-	-	n/a
712A™	Sprayout Clearcoat (Aerosol)	Exempt: Non-refillable aerosol products	RTS	-	-	n/a
LE5100S™	Clearcoat		2:1	LE11X5S	-	3.5
LE5400S™	Clearcoat		4:1	LE11X0S	-	3.5
LE5600S™	Clearcoat		4:1:1	LE5605S™	LE56X5S	3.5
LE8300S™	Clearcoat		3:1:1	LE100XS	LE10X5S	3.5
LE8700S™	Clearcoat		3:1	LE100XS	-	3.5

## Three-Stage Topcoats: VOC Limit = 3.5 lbs./gal. (420 g/L)

Must be used with specified Clearcoats or Basecoat for compliance, please consult technical data sheet. Additional additives may be used.

CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
1000XS	Midcoat		2:1	LE11X5S	-	3.5
72500S™	Clearcoat		2:1:10%	1230XS	123X5S	3.5
F Quality	ChromaPremier® Basecoat		1:1:6.25%	71X5S	1430XS / 77X5S	3.5
FX Quality	ChromaLusion® Basecoat		1:1:6.25%	71X5S	12305S™	3.5
K Quality	ChromaBase® Basecoat		1:1:6.25%	71X5S	1430XS / 77X5S	3.5

⚠ - Please see Technical Data Sheet for usage and mixing recommendation; Exempt, non-refillable aerosol products.

Group 2 Vehicles : Public transit buses and mobile equipment - where color match is not required.

All VOC (LE) values listed are Maximum Ready-to-Spray in pounds per gallon

Hardener = Activator  
X = 1, 2, 3, 4, 5, 6, 7, 8, 9

AN AXALTA COATING SYSTEMS BRAND

© 2018 Axalta Coating Systems, LLC and all its affiliates. All rights reserved.

1-855-6 AXALTA  
CROMAX.US