




Metacryl 7374 Strong Surface Cleaner




7374
Strong Surface Cleaner

COMPONENTS




N/A

APPLICATION




Ready to Use

MIX RATIO




N/A

DRY TIME



N/A

VISCOSITY



3.43 lbs/gal
411 g/L

VOC



GENERAL

DESCRIPTION

Metacryl 7374 Strong Surface Cleaner is a strong, medium drying surface cleaner designed specifically for removing tar, wax, oil, grease, road grime, silicone and surface contaminants prior to sanding or body work.

COMPATIBLE SUBSTRATES

- Properly prepared steel, aluminum and galvanized steel
- Thoroughly sanded OEM finishes
- Properly sanded and cured paint
- Cured body filler

The products referenced herein may not be sold in your market. Please consult your distributor for product availability.



MIXING

COMPONENTS

Shake can prior to use. Product is ready to use.

Component	Volume
Metacryl 7374 Strong Surface Cleaner	1



APPLICATION

SURFACE PREPARATION

- Prep surface by cleaning with warm, soapy water. Rinse thoroughly and allow to dry. If there is exposed bare steel, towel dry to prevent flash rusting.

APPLICATION

- Saturate a clean, dry, lint-free cloth and apply to one panel at a time.
- Follow by wiping with a second clean, dry, lint-free cloth until dry.
- Metacryl 7374 is a strong cleaner. Do not use on fresh paint as it may dull the finish.

CLEAN-UP

Clean spray equipment immediately following application with a quality thinner or spray gun cleaner. Dispose of all paint and paint related materials in accordance with state and local regulations.



PHYSICAL PROPERTIES

VOC as Applied	3.43 lbs./gallon (411 g/L)
Weight Solids	43.86%
Product Class	Specialty product

STORAGE CONDITIONS

Store in a dry, well ventilated area. Storage temperatures should be between -30°F (-34°C) and 120°F (48°C).

VOC REGULATED AREAS

VOC as Applied	411 grams/liter 3.43 lbs/gallon
----------------	-----------------------------------

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: March 2019

In the United States and Canada:
1.855.6.AXALTA
metacryl.us

