



Metacryl 7375 Zero VOC Surface Cleaner



7375
COMPONENTS Zero VOC Surface Cleaner



N/A
APPLICATION



Ready to Use
MIX RATIO



N/A
DRY TIME



N/A
VISCOSITY



0.0 lbs/gal
 0 g/L
VOC



GENERAL

DESCRIPTION

Metacryl 7375 Zero VOC Surface Cleaner is a ready to use, zero VOC water-based surface cleaner designed specifically for areas with low VOC regulations. This medium drying cleaner may be used on bare metal without concern for immediate flash rusting and on plastic to minimize static buildup.

COMPATIBLE SUBSTRATES

- Properly prepared steel, aluminum and galvanized steel
- Thoroughly sanded OEM finishes
- Properly sanded and cured paint
- Cured body filler

The products referenced herein may not be sold in your market. Please consult your distributor for product availability.



MIXING

COMPONENTS

Shake can prior to use. Product is ready to use.

Component	Volume
Metacryl 7375 Zero VOC Surface Cleaner	1



APPLICATION

SURFACE PREPARATION

- Prep surface by cleaning with warm, soapy water. Rinse thoroughly and allow to dry. If there is exposed bare steel, towel dry to prevent flash rusting.

APPLICATION

- Saturate a clean, dry, lint-free cloth and apply to one panel at a time.
- Follow by wiping with a second clean, dry, lint-free cloth until dry.
- In low temperature applications, be sure to dry the surface completely before applying primers or topcoats. Additional heat or air movement may be used to speed the solvent evaporation.
- Protect from freezing. Best used when temperatures are maintained at or above 70°F/21°C. Do not use on solvent sensitive substrates.

FOR GALVANIZED / ALUMINUM

- Scuff the surface with a soaked scotch brite pad, wash with warm water and towel dry. Topcoat within 30-minutes using 7396 or 7394 for best results.

CLEAN-UP

Clean spray equipment immediately following application with a quality thinner or spray gun cleaner. Dispose of all paint and paint related materials in accordance with state and local regulations.



PHYSICAL PROPERTIES

VOC as Applied	0.0 lbs./gallon (0 g/L)
Weight Solids	11.04%
Product Class	Specialty product

STORAGE CONDITIONS

Store in a dry, well ventilated area. Storage temperatures should be between -30°F (-34°C) and 120°F (48°C).

VOC REGULATED AREAS

VOC as Applied 0 grams/liter | 0.0 lbs/gallon

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.



SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: May 2019

In the United States and Canada:
1.855.6.AXALTA
metacryl.us

