



# Metalux™ 1174 Super Blend Reducer



---

## GENERAL

### DESCRIPTION

1174 Super Blend Reducer is a specially formulated solvent designed to dissolve edges of fade-out areas invisibly into the background during the process of spraying topcoats (making spot repairs). Super Blend Reducers can be used in MS Clears and 2K Polyurethane Color.

### Package Sizes

- 1 quart (0.94 liters)
- 1 gallon (3.75 liters)



---

## APPLICATION

### APPLICATION

Mix 1174 at ratio 1:1 with Hardened Clear after final full coat of clear has been applied. Spray a coat beyond previous coat. Dump clear out of gun. DO NOT clean gun. Then pour in enough 1174 for a final, lower pressure coat beyond all previous coats.

---

## VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

---

## SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: July 2018

In the United States and Canada:  
**1.855.6.AXALTA**  
**metalux.us**

