



# Montana Big Sky™ TH5951 Mild Wax & Grease Remover



## GENERAL

### DESCRIPTION

TH5951 is milder and slower to evaporate than TH5950 Wax & Grease Remover and is designed specifically for use after priming and sanding.

**The products referenced herein may not be sold in your market. Please consult your distributor for product availability.**



## APPLICATION

### APPLICATION

1. Saturate a clean, dry lint-free cloth with TH5951 Mild Wax & Grease Remover and apply to one panel at a time or for large areas, apply to a 2' x 2' section to avoid premature drying.
2. Follow by wiping with a clean dry lint-free cloth until dry. Be sure to dry the surface completely before applying primers or topcoats.

Note: TH5951 may be used as a general purpose tar and bug remover.

## VOC REGULATED AREAS

VOC as Applied

772 grams/liter | 6.44 lbs/gallon

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

## SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: May 2019

In the United States and Canada:

**1.855.6.AXALTA**  
**montanabigsky.us**

