

Low VOC Chart

For Eastern Kern APCD - Rule 410.4A
Motor Vehicle and Mobile Equipment Refinishing Operations



Effective: March 13, 2014

Revised: March 2019

Compliant Aerosol Coating Products Rule 410.4A Exemption			
CODE	DESCRIPTION	CODE	DESCRIPTION
402-01™	Gloss Trim Black	421-24™	Gray Primer
402-02™	Flat Trim Black	421-25™	Red Oxide Primer
402-03™	Semi Gloss Trim Black	421-26™	Beige Primer
403-00™	Clearcoat	492-51™	Undercoating

Cleaning Solvents VOC Limit 25 g/L (.21 lb/gal) - Note in footer			
CODE	DESCRIPTION	REMARKS	APPLIED VOC
105™	Cleaner	¥ See Footer	650 g/L
106™	Cleaner	¥ See Footer	528 g/L
107™	Gun & Equipment Cleaner		25 g/L
108™	Low HAP Cleaner	¥ See Footer	472 g/L
130™	Cleaner		0 g/L
139™	Cleaner	¥ See Footer	347 g/L
220™	Silicone Remover Low VOC	¥ See Footer	25 g/L
225™	Bug & Tar Remover	¥ See Footer	347 g/L
265™	Plastic Cleaning Paste	¥ See Footer	25 g/L
441-05™	Cleaner	¥ See Footer	778 g/L
441-75™	Cleaner	¥ See Footer	779 g/L

Pretreatment Coating VOC Limit 660 g/L (5.5 lb./gal)					
CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
491-55™	Chrome-Free Etch Primer	2:1	-	441-55™	660 g/L

Adhesion Promoter VOC Limit 540 g/L (4.5 lb./gal)					
CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
491-50™	Adhesion Promoter	-	-	-	540 g/L

Primer VOC Limit 250 g/L (2.1 lb./gal)					
CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
421-1X	Primer (⚠ - Note in footer)	4:1	483-03™	-	250 g/L
421-30™	Primer Surfacer	1:1	-	441-60™	250 g/L

Primer Sealer VOC Limit 250 g/L (2.1 lb./gal)					
CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
421-1X	Sealer (⚠ - Note in footer)	3:1:2	483-03™	401-X5	250 g/L
491-1X	Primer Sealer	2:1	483-01™ / 483-02™	-	250 g/L

Single Stage Coating VOC Limit 340 g/L (2.8 lb./gal)					
Additional additives may be used. Consult technical data sheet for usage and compliance.					
CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
IS	Ful-Thane® Single Stage Topcoat	4:1:2	483-56™	441-6X	340 g/L
412-01™	Ful-Thane® Single Stage Topcoat	4:1:2	483-56™	441-6X	340 g/L
412-50™	Ful-Thane® Single Stage Topcoat	4:1:2	483-56™	441-6X	340 g/L

Color Coating VOC Limit 420 g/L (3.5 lb./gal)					
Additional additives may be used. Consult technical data sheet for usage and compliance.					
CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
IR	Ful-Base® Basecoat	1:1	‡ See Footer	441-6X	420 g/L

Clear Coating VOC Limit 250 g/L (2.1 lb./gal)					
CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
462-00™	Clearcoat	4:1	483-84™ / 483-85™	-	250 g/L
468-00™	Clearcoat	4:1	483-84™ / 483-85™	-	250 g/L
468-00™	Clearcoat	3:1	483-86™	-	250 g/L
476-00™	Clearcoat	2:1	483-64™ / 483-65™	-	250 g/L

Other components that may be used (list is not all-inclusive). Consult technical data sheet for usage and compliance.					
CODE	DESCRIPTION	CODE	DESCRIPTION		
401-22™	Low VOC Gloss Enhancer	441-83™	Low VOC Flow Additive		
495-02™	Topcoat Additive				

¥ Plastic cleaning; applied with non-aerosol, hand-held spray bottle; total volume cannot exceed 20 gallons year, per facility.

‡ Optional Activation: Add 1 oz. 483-56™ RTS quart

⚠ - Refers only to products 421-10™, 421-11™ & 421-12™

An Axalta Coating Systems Brand

© 2017 Axalta Coating Systems, LLC and all its affiliates. All rights reserved.

X = 0, 1, 2, 6, 8

*Less Water, Less Exempt
1-855-6 AXALTA
nasonfinishes.com