

# Standex® VOC Compliance Chart

Group 1 Vehicles : Cars, large-heavy duty trucks, light/medium duty trucks, vans and motorcycles.  
 Butte County AQMD Rule 235 - Effective 07/01/1999  
 Colusa County APCD Rule 2.42 - Effective 07/01/2000  
 Shasta County AQMD Rule 3:25 - Effective 07/01/1998  
 Tehama County APCD Rule 4:35 - Effective 07/01/1999



Description	Article #	Compliant Rules				Applied VOC g/L	Remarks
<b>Surface Preparation VOC Limit = 1.67 lbs/gal (200 g/L)</b>							
Standex® Low VOC Plastic Cleaner	16010					21	
Standex® Cleaner	16176					188	
Axalta® 107™ Low VOC Gun & Equipment Cleaner	107					25	
Axalta® 210™ Silicone Remover Water	210					167	
Axalta® 130™ Cleaner	130					1	
Axalta® 265™ Plastic Cleaning Paste	265					0	
Axalta® 220™ Silicone Remover Low VOC	220					25	
Standex® VOC Cleaner 25	16178					25	
<b>Surface Preparation (Plastic) VOC Limit = 6.5 lbs/gal (780 g/L) if applied from hand-held spray containers</b>							
Axalta® 200™ Silicone Remover Slow	200					780	
Standex® Silicone Remover Antistatic	16203					773	Must be applied with a spray bottle for compliance.
<b>Butte, Colusa, Shasta, Tehama</b>							
Description	Article #	Mix Ratio	Hardener	Thinner/ Additive	Addl Product	Max Applied VOC (LE) g/L	Remarks
<b>Pre-treatment VOC Limit = 6.5 lbs/gal (780 g/L)</b>							
Axalta® 400A™ 1K Primer Surfacar Dark Gray	400A	1:1	N/A	N/A	N/A	N/A	
Axalta® 410A™ 1K Primer Surfacar Light Gray	410A	Ready to Use	N/A	N/A	N/A	N/A	
Axalta® 420™ Etch Primer	420	1:1	421	N/A	N/A	780	
Axalta® 495™ Metal Pretreatment Wipes	495	Ready to Use	N/A	N/A	N/A	780	
Standex® 1K Primer (Aerosol)	16196	Ready to Use	N/A	N/A	N/A	N/A	
Standex® 1K Primer	16134	+50%	N/A	2K Thinners	N/A	780	
Standex® Etching Adhesion Primer	16167	1:1	16168	N/A	N/A	780	
Standex® Low VOC Etch Primer	16189	2:1	16190	N/A	N/A	780	
Standex® 1K Primer (Aerosol)	16141/16228	Ready to Use	N/A	N/A	N/A	N/A	
Axalta® Pretreatment Wipes	PS4000™	Ready to Use	N/A	N/A	N/A	780	
<b>Primers/Primer Surfacers VOC Limit = 2.8 lbs/gal (340 g/L)</b>							
Standex® PF Filler	16220/16221	5:1+10-20%	PF Hardeners	16215, 16224, 16225	N/A	340	
Standex® PF Filler w/2K Plasticiser	16220/16221	5:1 +10-20%	PF Hardeners	16215, 16224, 16225	+15% 15260	340	15260 must be added before hardener.
Standex® 1K Waterborne Primer Surfacar	16231	1+5-15%	N/A	80188		340	
<b>Primer Sealers VOC Limit = 3.5 lbs/gal (420 g/L)</b>							
Axalta® 460A™ Epoxy 2K	460A	Ready to Use	N/A	N/A	N/A	N/A	
Standex® PF Sealer	16222/16223	4:1+30%	PF Hardeners	16224, 16225	N/A	420	
Standex® PF Sealer w/2K Plasticiser	16222/16223	4:1+30%	PF Hardeners	16224, 16225	+15% 15260	420	15260 must be added before hardener.
Standex® 2K EP Primer (Aerosol)	16181	Ready to Use	N/A	N/A	N/A	N/A	
<b>Single Stage Topcoats VOC Limit = 5.0 lbs/gal (600 g/L)</b>							
Standex® 2K MS	See Price List	2:1+0-10%	2K Hardeners	2K Thinners	N/A	600	
Standex® 2K MS w/2K Plasticiser	See Price List	2:1+0-10%	2K Hardeners	2K Thinners	+15-30% 15260	600	15260 must be added before hardener.
<b>Multistage Topcoat VOC Limit = 5.0 lbs/gal (600 g/L) applied as a 2-stage or 3-stage coating system</b>							
<b>Basecoats: Must be used with specific clearcoats for compliance</b>							
Standex® Basecoat	See Price List	+50%	N/A	MSB Thinners	N/A	600	
Standex® Basecoat	See Price List	+15%+30-40%	2.1 Hardeners	MSB Thinners	N/A	600	Only compliant if used in a 2-stage coating system with 2.1 Clear (10020), 2.1 HS Clear (16156), or 2k HS Clear (14580).
Standex® Basecoat Real Black	14017	+15%+40%	2.1 Hardeners	MSB Thinners	N/A	600	Only compliant if used in a 2-stage coating system with 2.1 Clear (10020), 2.1 HS Clear (16156), or 2k HS Clear (14580).
<b>Clearcoats: Must be used as a system with basecoats at/under 5.0 lbs/gal (600 g/L) for compliance</b>							
Standex® 2K HS Clear	14580	2:1+0-5%	2.1 Hardeners	2.1 Thinners	N/A	600	Not compliant if used in a 3-stage coating system with Standox Basecoat.
Standex® 2K MS Clear w/2K Plasticiser	14580	2:1+0-5%	2.1 Hardeners	2.1 Thinners	+15-30% 15260	600	Not compliant if used in a 3-stage coating system with Standox Basecoat. 15260 must be added before hardener.
Standex® VOC Platinum Clear	16161	2:1	2.1 Hardeners	N/A	N/A	600	Not compliant if used in a 3-stage coating system with Standox Basecoat.
Standex® Clear PFC 20	16211/ 16217	2:1+15%	PF Hardeners	16215	N/A	600	Not compliant if used with hardened Standox Basecoat.
Standex® Clear PFC 20 w/2K Plasticiser	16211/ 16217	2:1+15%	PF Hardeners	16215	+10-15% 15260	600	Not compliant if used with hardened Standox Basecoat. 15260 must be added before hardener.
Standex® Clear PFC 30	16216	2:1+5%	PF Hardeners	16215	N/A	600	
Standex® Clear PFC 30 w/2K Plasticiser	16216	2:1+10%	PF Hardeners	16215	+10-15% 15260	600	15260 must be added before hardener.
Standex® Clear PFC Air Dry	16218	4:1 +20%	PF Hardeners	16215	N/A	600	
Standex® Clear PFC Air Dry w/2K Plasticiser	16218	4:1 +20%	PF Hardeners	16215	+10% 15260	600	15260 must be added before hardener.
Standex® 2K Matting Agent Mix 608 w/16216 Satin Finish	16199	5:1 w/16216	2:1 w/ 16214	+20% PF Thinner	N/A	600	
Standex® 2K Matting Agent Mix 608 w/16216 Flat Finish	16199	6:1 w/16216	2:1 w/ 16214	+20% PF Thinner	N/A	600	
<b>Specialty Coatings VOC Limit = 7.0 lbs/gal (840 g/L) - Cannot exceed 5% paint volume on a monthly basis.</b>							
<b>Elastomeric Coatings</b>							
Standex® Plastic Primer Silver	12065	Ready to Use	N/A	N/A	N/A	840	
Standex® Plastic Primer Silver (Aerosol)	14409	Ready to Use	N/A	N/A	N/A	840	EXEMPT
Standex® 1K Plastic Adhesion Primer	16202/16227	Ready to Use	N/A	N/A	N/A	840	
Standex® 2K Plastic Primer Surfacar	11816/16192	1:1	11824	N/A	N/A	840	
Standex® 2K Matte Clear 007 (alone or per TDS)	16163	3:1+0-25%	2K Hardeners	2K Thinners	N/A	840	
Standex® 2K Rallye Matte Black	10887	3:1+0-10%	2.1 Hardeners	2K Thinners	N/A	840	
<b>Uniform Finish Coatings</b>							
Standex® Basecoat Colorless	16150	Ready to Use	N/A	or +10% MSB Thinners	N/A	840	
Standex® Basecoat Colorless	16150	1:2 w/Standox® Basecoat (RTS)				840	
Standex® Basecoat Colorless	16150	15%	2.1 or 2K Hardeners	N/A	N/A	840	
Standex® 2k Smart Blend Plus	16174	4:1 w/2K Clear (RTS)				840	
Standex® 2k Smart Blend Plus w/PFC 20 (16211)	16174	See TDS 1206 for compliant mixing recommendations				840	
Standex® 2k Smart Blend Plus w/PFC 30 (16216)	16174	See TDS 1206 for compliant mixing recommendations				840	
Standex® Color Blend	19310/19311	+5-10%	N/A	19301, 19302, 19303	+5% 18316	840	
Standex® Color Blend	19310/19311	+0-5%	N/A	18316	N/A	840	
Standex® 2K Fade-Out Thinners 11031	11247	3:1 w/RTS 2K Clear	N/A	N/A	N/A	840	
<b>Other Products - Consult technical data sheet for usage and compliance.</b>							
Standex® Additive Blue	16255	See TDS	N/A	N/A	N/A	600	
Standex® Additive Maroon	16256	See TDS	N/A	N/A	N/A	600	
Standex® Additive Magenta	16257	See TDS	N/A	N/A	N/A	600	
Standex® Additive KA679 Bright Red	16679	See TDS	N/A	N/A	N/A	600	
Axalta® 766A™ 1K Trim Black Satin	766A™	Ready to Use	N/A	N/A	N/A	N/A	
Axalta E-Coat Restore Aerosols	See Price List	Ready to Use	N/A	N/A	N/A	N/A	
Axalta® 715™ Sanding Paste	715™	Ready to Use	N/A	N/A	N/A	N/A	
Standex® Sanding Paste	14670	see TDS	N/A	N/A	N/A	N/A	

For complete product usage and mixing recommendations, see the product specific technical data sheet located on [www.standex.com](http://www.standex.com).  
 Copyright © 2021 Axalta Coating Systems. Standox® and all products designated with TM or ® are trademarks or registered trademarks of Axalta Coating Systems for its brands of refinsh systems. All rights reserved.