

Transportation VOC Chart

For the State of Indiana

326 IAC 8 Rule 10 - Automobile Refinishing

Revised: November 2019

Effective: June 1, 2009



Surface Cleaner VOC Limit 1.4 lbs./gal (168 g/L) | Plastic Surface Cleaner Limit 6.5 lbs./gal (780 g/L)

CODE	DESCRIPTION	REMARKS	MIX RATIO			APPLIED VOC
105™	Cleaner	Plastic Parts Only!	-			5.4
106™	Cleaner	Plastic Parts Only!	-			4.4
107™	Low VOC Cleaner		-			0.2
108™	Low HAP Cleaner	Plastic Parts Only!	-			3.9
130™	Low VOC Cleaner		-			0.0
3800S™	Cleaner	Plastic Parts Only!	-			6.5
3812S™	Cleaner	Plastic Parts Only!	-			5.6
3821S™	Low VOC Cleaner		-			0.2
3850S™	Cleaner	Plastic Parts Only!	-			5.4
835S™	Cleaner	Plastic Parts Only!	-			6.5

Specialty Coating VOC Limit | 7.0 lbs./gal. (840 g/L)

CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
230S™	Adhesion Promoter		2:98	-	DI Water	7.0
231XS	Sanding Paste	Ready to use	-	-	-	7.0
3401S™	Blender	¥ - Note in footer	-	-	-	7.0
6650S™	Blender	¥ - Note in footer	16:1	15305S™/15309S™/294S™	-	7.0
830S™	Adhesion Promoter	Ready to use	-	-	-	7.0

Pretreatment VOC limit | 6.5 lbs./gal. (780 g/L)

CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
225S™	Aluminum Metal Cleaner - Step A		1:2	-	water	6.5
226S™	Aluminum Conversion Coating - Step B		RTS	-	-	0.0
235S™	Pretreatment		4:1	236S™	-	6.5
244S™	Pretreatment		RTS	-	-	6.5
250-S™	Pretreatment		1:1	255S™	-	6.5
5717S™	Pretreatment		1:2	-	water	6.5
5718S™	Pretreatment		RTS	-	-	0.0
CF-5717S™	Pretreatment		1:2	-	water	6.5

Primer / Primer-Surfacer VOC Limit | 4.8 lbs./gal. (580 g/L)

Other additives may be used. Consult technical data sheet for usage requirements.

CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
1220S™	Primer		4:1	194S™	-	4.8
1480S™	Primer		4:1	1481S™ / 1489S™	-	4.8
RV400™	Rival™ Urethane Primer		6:1	RV128™ / RV135™	-	4.8

Primer-Sealer VOC Limit | 4.6 lbs./gal. (550 g/L)

Other additives may be used. Consult technical data sheet for usage requirements.

CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
821CR™	DTM Primer		2:1	82XS	-	4.6
92XS	Primer		2:1	92XS	-	4.6
934S™	Primer Sealer		5:1	936S™	-	4.6
1340S™	Primer Filler		4:1	194S™	-	4.6
1380S™	Primer Filler		4:1	194S™	-	4.6
185XS	Primer		4:1	1852S™	-	4.6
RV450™	Rival™ Epoxy Primer Sealer		4:1	RV455™	-	4.6

Single Stage Topcoat VOC Limit | 5.0 lbs./gal. (600 g/L)

Other additives may be used. Consult technical data sheet for usage requirements.

QUALITY	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
A	Centari® Single Stage Topcoat		8:1:2	793S™	80XXS	5.0
EA	Imron® Elite Single Stage Topcoat		3:1	194S™	-	5.0
EF	Imron® Elite Express Single Stage Topcoat		3:1	196S™	-	5.0
EU	Imron® Single Stage Topcoat		3:1	V-192S™	-	5.0
EX	Imron® Elite Productive Single Stage Topcoat		3:1 / 2.5:1	1530XS / 15309S™	-	5.0
EZ	Excel™ Pro Single Stage Urethane		4:1 / 2.5:1	1530XS / 15309S™	-	5.0
RV28/35	Rival™ Single Stage		6:1	RV128™ / RV135™	-	5.0
EX28	Imron® Elite Productive Single Stage Topcoat		3:1	15309S™	-	5.0

Multi-Stage Topcoat VOC Limit | 5.0 lbs./gal. (600 g/L) - Other additives may be used, consult technical data sheet for usage.

Must be used with specified clearcoats for compliance. Consult technical data sheet.

QUALITY	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
CT	Imron® Basecoat	¥ - Note in footer	4:1:12	15305S™/15309S™/294S™	66X5S	5.0
EW	Imron® Elite Productive Basecoat		3:1	1530XS	-	5.0
EB	Imron® Elite Basecoat		3:1	194S™	-	5.0
EG	Imron® Elite Express Basecoat		3:1	196S™	-	5.0
EK	Excel™ Pro Basecoat		4:1	1530XS	-	5.0
EY	Imron® Elite Productive Basecoat		3:1	294S™	-	5.0

Multi-Stage Topcoat VOC Limit | 5.0 lbs./gal. (600 g/L) - Other additives may be used, consult technical data sheet for usage.

Must be used with specified basecoats for compliance. Consult technical data sheet.

CODE	DESCRIPTION	REMARKS	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)
500S™	Clearcoat		3:1	V-192S™	-	5.0
8430S™	Clearcoat		2:1	1530XS	-	5.0
EZ-3460S™	Clearcoat		3:1	EZ-3461S™	-	5.0
3480S™	Clearcoat		3:1	194S™	-	5.0
3430S™	Clearcoat		3:1	1530XS	-	5.0
8460S™	Clearcoat		2:1	1530XS	-	5.0
8461S™	Clearcoat		2:1	1530XS	-	5.0
8821S™	Clearcoat		3:1	15309S™	-	5.0
8831S™	Clearcoat		3:1	15309S™/15310S™	-	5.0
8840S™	Clearcoat		3:1	194S™	-	5.0
8890S™	Clearcoat		3:1	294S™	-	5.0
RV500™	Rival Clearcoat		6:1	RV128™ / RV135™	-	5.0

Other components that may be used, please consult technical data sheet for usage and compliance. This list is not all-inclusive.

CODE	DESCRIPTION	REMARKS	CODE	DESCRIPTION	REMARKS
89S™	Pot Life Extender		19379S™	Application Enhancer	
189S™	Accelerator		236XS™	Matting Agent	
389S™	Accelerator		8989S™	Accelerator	
459S™	Anti-Cratering Additive		V-2350S™	Flex Additive	
X59S™	Additive		V-389S™	Accelerator	
VG70050	Anti-Cratering Additive		2350S™	Flex Additive	

¥ Please see Technical Data Sheet for usage and mixing recommendation.

All VOC (LE) values listed are Maximum Ready-to-Spray in pounds per gallon

X = 1, 2, 3, 4, 5, 6, 7, 8